



Product Range & Ordering Details

Part Number	Description
SURFACE MOUNT	
CAPRICE-HF-2D6	16w 2D lamp
CAPRICE-HF-325/22W	22w T5 circular lamp
CAPRICE-HF-22W	22w T5 circular lamp
CAPRICE-HF-40W	40w T5 circular lamp
SEMI-RECESSED	
CAPRICE-HF-22W-REC	22w T5 circular lamp
CAPRICE-HF-40W-REC	40w T5 circular lamp

Other lamp sources such as 28w 2D are available upon request

*Notes to the above codes
Prismatic diffuser is supplied as standard
If Opal diffuser is required suffix code with "OP"

Please use correct code for order requirement

For integral self contained 3 hour emergency pack, add EM3 at the end of the code.

The main housing of the luminaire can be white, brass or chrome – add the following suffixes to the code:-

White – WH
Brass – BS
Chrome – CH

Movement Controlled Dimmable Lighting System

The CAPRICE 22w and 40w is suitable for use with the Movement Controlled Dimmable Lighting System for energy efficiency based on occupancy. Please ask for our brochure on this range.

Description

A range of slim stylish luminaires incorporating many features which make their application possibilities endless. Available for surface mounting in either 325mm diameter or 420mm diameter or for semi-recessing at 452mm diameter.

The luminaire consists of a main body that is vented to ensure sufficient airflow, resulting in reduced heat build-up. It is fitted with a removable gear tray with all control gear located on the rear side, avoiding heat contamination from the lamp.

The luminaire is fitted with high frequency control gear as standard and is designed to offer energy efficiency by utilising the latest in lamp technology. Whilst various lamp options are available the T5 circular lamp provides high output lighting levels and is supplied with either a prismatic diffuser or with an opal diffuser for more discreet illumination.

IP Rating

IP20

Applications

- Nursing Homes
- Hospitals
- Schools & Colleges
- Corridors Lighting
- Entrance Lobbies

Features

- Tough spun steel construction
- Removable gear tray
- Energy efficient lamp sources
- Integral emergency options

Options & Accessories

Part Number	Description	For use with
HF	High Frequency Gear	
HFD	High Frequency Dimmable	Not 16 or 28 w 2D
NL	Nite Light Facility	7 w PLLStandard
EM3	3 Hour Maintained Emergency	*Indicated
RK	Recessing Kit or Trim	CAPRICE-REC

*Available with Integral Emergency

Dimensions (mm)

Part Number	A	H	F/C
CAPRICE-HF-325/22W	325	90	3 Holes 180 PCD & Besa
CAPRICE-22W or 40W	430	100	3 Holes 240 PCD & Besa
CAPRICE-22W or 40W REC	425	90	3 Holes 240 PCD & Besa

