



Description

As a complement to our Caprice luminaire range the Gemini offers a backlight to give extra illumination and effect. It can be suspended by catenary wires or surface mounted direct to the ceiling.

The luminaire is fitted with high frequency control gear as standard and is designed to offer energy efficiency by utilising the latest in lamp technology. Whilst various lamp options are available the T5 circular lamp provides high output lighting levels. The luminaire can also be supplied with dimmable high frequency control gear.

IP Rating

IP20

Product Range & Ordering Details

Part Number	Description
GEMINI-HF-22W	22w T5 circular lamp
GEMINI-HF-40W	40w T5 circular lamp
GEMINI-HF-55W	55w T5 circular lamp
GEMINI-HF-2D8	28w 2D lamp

*Notes to above product codes

Prismatic diffuser is supplied as standard

If Opal diffuser is required suffix code with "OP"

Please use correct code for order requirement

For High Frequency Dimmable Gear, change HF to HFD

For Integral self contained 3 hour Emergency Pack, add EM3 at the end of the code

The front spinning can be white, brass or chrome – add the following suffixes to the code:-

White – WH

Brass – BS

Chrome – CH

Construction

Spun steel front and gallery with the option of prismatic or opal polycarbonate diffuser.

Features

- Stylish Design
- Back Light
- Can be used as a pendant

Applications

- Stairwells
- Entrance Lobbies
- Corridors
- Reception & Lounge areas
- Doctors Surgeries

Energy Efficiency

Suitable for occupancy detection and daylight linking. The Gemini Luminaire is compatible with many of the Morgan-Hope lighting control systems

Dimensions (mm)

	A	B	C
GEMINI	526	458	104

