

Low profile emergency surface/recessed luminaire/exit sign

Manufactured from Flame-Retardant Polycarbonate, this elegantly designed IP55 Luminaire is suitable for almost any prestigious application.

Dalby can be used for surface or recessed mounting (when recessed only 25mm protrudes below the ceiling) and with the addition of a Self-Adhesive Legend, a simple but attractive Exit sign is created.

The **Dalby** design also offers an Edge-Lit Exit sign version which can be confidently specified for projects including Hotels and Reception areas.

Dalby's diffuser design incorporates a light-pipe ensuring the LED charge indicator is visible in all modes.

Dalby surface mounted



Dalby recessed with edge lit exit legend

Viewing distance 32 metres



SAL2 provides several options for an exit legend.

Viewing distance 22 metres

Mains Luminaires

Cat No.	Mode/Lamp	Lumens	Kg
DAL8	8W 300mm Mains		1.35

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
DAL8/NM3	NM3 8W 300mm	80E	1.80
		120S	
		180H	
DAL2x8/NM3	NM3 2x8W 300mm	240S	3.00
		360H	
DAL8/M3	M3 8W 300mm	80E	2.00
		120S	
		180H	

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
DAL8/#/D	8W Slave Luminaires	275	1 10

Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage

For other durations, specify the required time period e.g. /NM3 but for 1 hour duration becomes /NM1

Dimensions: Length 355mm x Width 195mm x Depth 70mm

Dalby Exit Dimensions: Length 355mm x Width 195mm x Depth 220mm

Cut out dimensions: Length 335mm x Width 175mm

Options Suffix:

/H	High Output	/AD	Intelligent Addressable Luminaires
/E	Economy Output		
/S	Standard Output	/ST	Self Testing Luminaires
/SAL2	Self-adhesive Exit Legend Kit	/TS	Push to Test Switch
/HPF	Power Factor Corrected	/EX/L+	Edge-lit Exit Kit
/HF	High Frequency Ballast	/R	Recessing Kit
/ES	Electronic Start		