

Technical Specification

Ballast lumen factors for control gear incorporating Perform™ technology (suitable for all lamps including low Mercury & Amalgam lamps)

Module Number			Battery Cells			T8/T12							T5									
			18W	20W	30W	36W	40W	58W	70W	100W	8W	14W	21W	24W	28W	35W	39W	49W	54W	80W		
PH4003P3	PL4003P3	PLR5003P3	3 x 4Ah	12	12	9	9	9														
PH4005P3	PL4005P3	PLR5005P3	4 x 4Ah	11	11	10	10						20									
		MT5414P3	4 x 4Ah										32									
PH4007P3	PL4007P3	PLR5007P3	4 x 4Ah					10														
PH4403P3	PL4403P3	PLR5403P3	4 x 4Ah																			
PH4418P3	PL4418P3	PLR5418P3	4 x 4Ah	25	25							42	32									
PH4009P3	PL4009P3	PLR5009P3	5 x 4Ah		13	13																
PH4506P3	PL4506P3	PLR5506P3	5 x 4Ah											28	25	26						
PH4011P3	PL4011P3	PLR5011P3	5 x 4Ah					10	7													
		MT5528P3	5 x 4Ah											28	25	26						
		PHR5607P3	6 x 4Ah			18	18	18														
		PHR5608P3	6 x 4Ah						11	10												
		PHR5809P3	8 x 4Ah						15	14	9						27	24	20	17		
		MT5854P3	8 x 4Ah														27	24	20	17		
		PHR5108P3	10 x 4Ah							17	10											10

Ballast lumen factors for emergency control gear (not suitable for low Mercury and Amalgam lamps)

Module Number		Battery Cells		T5/T8						
		8W	18W	20W	30W	36W	40W	58W	70W	
M2019/3(NM)	MS2020/3(M3)	2 x 4Ah	26							
M2001P3(NM)	MS2001P3(M3)	3 x 4Ah	34	24						
MS2001P3		3 x 4Ah	34	24	24					
MS2003P3		3 x 4Ah			14	14	14			
MS2007P3		4 x 4Ah	29				12	10		
MS2011P3		5 x 4Ah				13	13	10	9	

Fixing centres

Module	A	B	C	D	E	Kg
PH	154	42	35	144	138	0.33
PL	203	42	28	193	187	0.34
PLR	216	42	28	206	200	0.35
PHR	216	42	35	206	200	0.54
MT5	350	28	28	230	–	0.34
M/MS	154	42	35	144	138	0.33

