

Larino

Elegant circular lighting range

Designed for universal application within any lighting project, the **Larino** range of luminaires are available in three diameters: 330mm, 430mm and 525mm.

Larino luminaires feature a spun metal base containing the control gear and energy saving compact fluorescent lamps. Models can be either mains only operation or, in selected versions, incorporate integral emergency gear.

Larino's base is available in a range of epoxy coated and plated finishes and can be supplied with a smooth, polished opal or clear prismatic diffuser.

New options include wire and rod suspension kits for that added elegant touch.

Larino is available as standard with a white base and opal diffuser.



Larino finished in brass



Larino finished in chrome



Mains Luminaires

Cat No.	Mode/Lamp	Lumens	Kg
LAR16	16W Size A	-	1.10
LAR28A	28W Size A	-	2.00
LAR28	28W Size B	-	2.10
LAR38	38W Size B	-	2.10
LAR226HF	2x26W Size C	-	2.60
LAR55	55W Size C	-	2.60

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
LAR16/M3	16W M3 Size A	200	2.70
LAR28/M3	28W M3 Size B	270	3.00
LAR38/M3	38W M3 Size B	625	3.00
LAR226/M3	2x26W M3 Size C	324	3.70
LAR55/M3	55W M3 Size C	450	3.70

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
LAR16/##/D	16W Size A	400	1.00
LAR28/##/D	28W Size B	500	2.00
LAR38/##/D	38W Size B	500	2.00

* Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage

* For other durations, specify the required time period e.g. /M3 becomes /M1 for 1 hour duration

Dimensions Size A Ø 330mm x 105mm

Dimensions Size B: Ø 430mm x 105mm

Dimensions Size C: Ø 525mm x 105mm

Options Suffix:

/BR	Brass Finish	/AD	Intelligent Addressable Luminaire
/CH	Chrome Finish		
/PR	Prismatic Diffuser	/ST	Self Testing Luminaire
/HPF	Power Factor Corrected	/WS2	Wire Suspension Kit
/HF	High Frequency Ballast	/RS2	Rod Suspension Kit (600mm)
/ES	Electronic Start		

IP20  