

IP65 single or double sided exit sign

Tiel is a robust IP65 ceiling mounted single or double sided white polycarbonate exit sign. Suitable for surface or semi-recessed installations.

Its IP65 rating and optional tamper resistant screws, make the **Tiel** a unique single or double sided sign for all public areas.

Tiel is supplied complete with two self-adhesive legends as standard (please specify) so that the installer can make up either a single sided or double sided sign.



Viewing distances
28 metres



Tiel recessed

Options Suffix:

/E	Economy Output	/HF	High Frequency Ballast
/S	Standard Output	/ES	Electronic Start
/H	High Output	/AD	Intelligent Addressable Luminaire (Non-Maintained Only)
/TI/WH	White Finished Semi-recess Trim	/ST	Digital Self Test (Non-Maintained Only)
/TI/BR	Brass Finished Semi-recess Trim	/TS	Push to Test Switch
/TI/CH	Chrome Finished Semi-recess Trim		
/VR	Anti-tamper Screws		
/HPF	Power Factor Corrected		

Mains Luminaires

Cat No.	Mode/Lamp	Lumens	Kg
TI8	1x8W 300mm	-	0.90
TI2x8	2x8W 300mm	-	0.90
TI11	11W TC-S	-	0.90

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
TI8/NM3	NM3 8W 300mm	80E 120S 180H	1.20
TI8/M3	M3 8W 300mm	80E 120S 180H	1.45
TI2X8/NM3	NM3 2X8W 300mm	150S 250H	1.70

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
TI8/#/D	8W Slave Luminaire	275	0.85

* Emergency Lumens

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage

* For other durations, specify the required time period e.g. /NM3 becomes /NM1 for 1 hour duration

Dimensions: Length 350mm x Width 108mm x Depth 204mm

Cut out dimensions: Length 330mm x Width 90mm

