



Features

- Fused in-line connector
- Removable Gear Tray
- High efficiency
- Low running costs
- Optional dimmable control gear
- Suitable for occupancy detection and daylight linking

Applications

- Factories
- Warehouses
- Sports Halls
- Plant Propagation

Description

Suitable for a wide range of applications where high light level installations are required. The luminaire can be mounted via hooks or onto conduit trunking or incorporated into a tee ceiling.

Product range and ordering details

Part Number	Lamp Type	Wattages
LOBY3PLL55	PLL	3 x 55 watt
LOBY4PLL55	PLL	3 x 55 watt

Dimensions

Part Number	Length (mm)	Width (mm)	Height (mm)	F/C
LOBY-PLL	605	450	1120	Besa @ 300mm 4 Holes 250 x 400mm

IP Rating

IP 20

Construction

Fabricated sheet steel body, which is welded and powder coated. The gear tray incorporates the lamps and reflectors and is fitted with a standard terminal block. The unit can have a 3 hour emergency pack fitted to one lamp, which is housed in a separate gearpod screwed to the end of the body.

Gear options

The EEL Lowbay is fitted with high frequency control gear as standard but can be supplied with dimmable control gear.

Occupancy detection and daylight linking

The EEL Lowbay is adaptable for use with occupancy detection and daylight linking and compatible with the Morgan-Hope range of lighting control systems.