



Features

- Fused in-line connector
- Removable Gear Tray
- High efficiency

Applications

- Factories
- Warehouses
- Sports Halls
- Plant Propagation

Product range

Lamp Type	Wattages
SON	150, 250, 400 & 600 watt
MBFU	250 & 400 watt
HQI	250 & 400 watt

Accessories

Part Number	Description	For use with
LB DIFF	Polycarb Dished Diffuser	150 & 250 watt
LB GLASS	Toughened Glass Cover	All - must be used with HQI
LB LOW	White Steel Louvre	All
LB-REF-HR	High Rack Reflector	250, 400 & 600 watt
LB GUARD	Wire Guard	All
LB PCGL	Polycarbonate sheet with toughened glass in special lowbay dims remain same	250 & 400 watt
LRM	Lamp Recognition Monitor For use with 200w Single Ended T Halogen lamp*	All Discharge Fittings

*Not supplied

Description

Suitable for wide range of applications where high light level installations are required. Suitable for mounting via hooks or onto conduit trunking or can be incorporated into a tee ceiling.

IP Rating

IP 20

Construction

Fabricated sheet steel body, which is welded and powder coated. The gear is mounted on a removable gear tray with an in-line fused connector. The reflector is manufactured from embossed high purity aluminium.

Ordering details

Part Number	Description
LOBY150SON	150 watt Son Lowbay c/w Lamp
LOBY250SON	250 watt Son Lowbay c/w Lamp
LOBY400SON	400 watt Son Lowbay c/w Lamp
LOBY250MBF	250 watt MBF Lowbay c/w Lamp
LOBY400MBF	400 watt MBF Lowbay c/w Lamp
LOBY250HQI	250 watt HQI Lowbay c/w Lamp
LOBY400HQI	400 watt HQI Lowbay c/w Lamp

Dimensions

Part Number	Length (mm)	Width (mm)	Height (mm)	F/C
LOBY	590	290	175	Besa @ 400mm