





- Its striking visual appearance and high level of efficiency makes the 6.66 Series
 a popular choice for many commercial and retail applications.
- Hard lacquered highly specular vacuum metalised diamond facet reflector manufactured from super-pure aluminium.
- Die-cast bezel finished in White RAL9010 Finetex, 20% gloss.
- Injection moulded UL94 VO flame retardent control gear / lampholder housings.
- New multi-wattage control gear available.
- Emergency versions manufactured in accordance with ICEL 1004:2003.

Please contact our Customer Services Department for a copy of our Relux® Lighting CD-ROM, which contains full photometric data.



Ordering Information

ordering information							
REF. No.	WATTAGE	CONTROL GEAR OPTIONS					
		HF	Multi-HF	DIM	ECO	DALI	EM
6.661018	18W						
6.661026-32	26-32W						
6.661026-42	26-42W			-			
6.661026	26W						
6.661032	32W						
6.661042	42W						
6.662018	2x18W						
6.662026-32	2x26-32W						
6.662026-42	2x26-42W						
6.662026	2x26W						
6.662032	2x32W						
6.662042	2x42W						



6.662026-42/HF DG201

Decorative opal dome feature glass



Accessories

- For the full range of decorative glass and bezel finishes, see page 30.
- Slimline versions, please add suffix /SV.
- Open cell ceiling fixing kits, see page 79.