

► **ospreysuper**  
0505 & 0510  
accessories



▲ **ospreystandard** (Utilises the same main body and gear housing as the **ospreysuper** but supplied with a fixed bezel as shown above)

## concept

Developed for leisure and commercial markets, the condensed design of the **osprey** mini-downlighter provides a universal luminaire that is an ideal alternative to low voltage downlighters.

The **osprey** series is a range of miniature downlights designed for commercial or retail applications where highly efficient, discreet lighting is required. The **osprey** features a 110mm die-cast bezel which incorporates a front recess, allowing the highly specular diamond facet reflector to locate within the bezel recess, ensuring good visual appearance with optimum performance.

The luminaire can incorporate a choice of high frequency control gear systems; HFM, HF and HFD modules, within a dedicated injection moulded housing, along with the lamp holder assembly.

This luminaire is suitable for Emergency Conversion. Specialist slimline modules were designed to pass through the 110mm cut out of the luminaire, where no access to the ceiling void exists.

To achieve optimum performance a revolutionary new air-vent system was developed. This allows air to be drawn into the luminaire through a primary or secondary air path. In the event that a sealed accessory is used, i.e. within a shower application, the secondary air path is utilised, maintaining a constant flow of air that is drawn into the chamber, which passes round the lamp, stabilising the pinch temperature. It is this cooling process that reduces the operating temperature of Electronic Control Gear resulting in optimum performance of the lamp.

## osprey air vent system



## osprey features

To simplify installation and offer maximum flexibility within the project, the entire **osprey** range utilises the same 95mm ceiling cut-out, allowing for last minute on-site design changes.

The **osprey** is available in two versions; the **ospreysuper** – a versatile mini-downlighter, boasting an extensive range of over 25 accessories, which simply locate within the Twist-and-Lock front bezel, allowing a choice of decorative, wall-wash or sealed options.

The **ospreystandard** is supplied with a fixed white bezel for applications that do not require the versatility of the accessories.

LED indicator  
for  
emergency  
lighting  
module



Fire Rated

LANTAC  
Certified

NHBC  
Approved

Miniature  
size –  
maximum  
performance

Integral  
Electronic  
Gear

# osprey compact fluorescent mini downlighter

## ospreysuper accessories

Accessories shown with alternative bezel finishes – please state finish required

bezel colour options

Wh	Ch	Go	Ba	Sp
----	----	----	----	----



**OS100 WH bezel**  
State finish required



**OS01**  
Prismatic clear dome



**OS01**  
Colour options:  
red/blue/green



**OS02**  
Clear prismatic cone



**OS02**  
Colour options:  
red/blue/green



**OS03**  
Recessed directional  
wall wash



**OS03**  
Colour options:  
red/blue/green



**OS04**  
Clear open cone



**OS04**  
Colour options:  
red/blue/green



**OS05**  
Decorative feature  
glass



**OS06**  
Sealed opal glass



**OS07**  
Vertical anti-glare filter



**OS08**  
Directional aluminium  
wall wash



**OS09**  
Feature glass with  
clear dome



**OS10**  
Decorative clear halo



**OS14**  
Sealed flush glass (clear)



**OS19**  
Perforated corona  
with blue lens

**Bezel type options:**

- OS100** Bezel for use with or without accessories
- OS05** Bezel with pre-fixed decorative glass will also accept OS01, OS06 & OS10 accessories.



## ordering information

When ordering please state: luminaire reference/lamp type/gear option

Reference	Wattage	Lamp type	GEAR OPTION			
			HF	HFM	DIM	EM
<b>ospreysuper</b> – FOR USE WITH TWIST-AND-LOCK ACCESSORIES						
MHA-6.901010	10	PLC	•	•	•	•
MHA-6.901013	13	DTE	•	•	•	•
MHA-6.901018	18	DTE	•	•	•	•
MHA-6.901026	26	DTE	•	•	•	•
<b>ospreystandard</b> – WITH FIXED WHITE BEZEL						
MHA-6.911010	10	PLC	•	•	•	•
MHA-6.911013	13	DTE	•	•	•	•
MHA-6.911018	18	DTE	•	•	•	•

The **ospreysuper** luminaire is supplied with a choice of bezel & accessory. Please refer to order/specification overleaf. Recessed wall wash version OS03 and OS14 flush glass are not available in 26W

To ensure lamp-gear compatibility we recommend all luminaires are supplied complete with lamp(s)

Specification and dimensions are for guidance purposes only, we reserve the right to amend any product specifications without prior notification