



FEATURES

- Stylish Design
- Slimline Body
- High Frequency Control Gear fitted as standard
- T5 High Efficiency Lamps as standard
- 20.000 Hour Lamp Life
- Option of Integral Emergency Gear
- Available with CAT 2 or Low Brightness Louvres or Prismatic Diffuser

Energy Efficient

Compact T5 Recessed Luminaire

DESCRIPTION

A stylish recessed luminaire for office or retail environments combining the latest developments in lamp technology with an aesthetically pleasing design. Constructed to fit into a 600mm x 600mm ceiling grid, this luminaire consists of a centrally positioned louvre and side wings incorporating a perforated design feature. Available in two models -600mm x 600mm x 3 lamp or 600mm x 600mm x 4 lamp the luminaire uses the T5 High Efficiency Lamp and is fitted with warm start High Frequency Control Gear

ENERGY EFFICIENCY

Whilst the T5 Lamp wattage rating is 14w as opposed to the T8 Lamp, which is 18w. the overall light output of the luminaire is comparable and as such provides an energy saving of 22%.

CONSTRUCTION

Fabricated steel body with fully welded construction, which is then iron phosphate pre treated, prior to the application of 100-micron epoxy polyester powder coat. The louvre is fitted with wishbone springs and is available either in CAT 2, or Low Brightness Louvres or Prismatic Diffuser

PRODUCT RANGE & ORDERING DETAIL DIMENSIONS

TL5R3X14

3 x 14 WATT T5 RECESSED MODULAR

595mm x 595mm x 70mm

TL5R4X14

4 x 14 WATT T5 RECESSED MODULAR

595mm x 595mm x 70mm

Suffix model type with CT2 for Category 2 Louvres, LBX for Low Brightness Louvres and PR for Prismatic Diffuser.

Nominal changes in sizes may occur due to manufacturing tolerances.



APPLICATIONS

- Offices
- Retail
- Commercial
- Banks

Morgan-Hope Industries Limited Units 5 and 6.

Blowick Industrial Park. Crowland Street, Southport, Merseyside PR9 7RU England Telephone 01704 512000 Fax 01704 542632

email info@morganhope.com website www.morganhope.com