



Description

Utilising the highly efficient PLL or T5 light source this new concept luminaire gives a gentle spread of even light, which also has the effect of lifting the apparent height of the ceiling.

Features

- High efficiency lamps and gear
- High lumen packages
- Category Two Compliant
- Pleasing effect
- Suitable for use with the Morgan-Hope lighting control systems

Applications

- Offices
- Entrance
- Lobbies
- Retail
- Showrooms

Product Range and Ordering Details

Part Number	Description
FLRA662x40PLL	2 x 40 w PLL Indirect/Direct Module
FLRA662x55PLL	2 x 55 w PLL Indirect/Direct Module
FLRA662x40PLL-CT2	2 x 40w PLL Indirect/Direct Module c/w Cat 2 Louvre
FLRA662x55PLL-CT2	2 x 55w PLL Indirect/Direct Module c/w Cat 2 Louvre
FLRA662x14T5-CT2	2 x 14w T5 Indirect/Direct Module c/w Cat 2 Louvre
FLRA662x24T5-CT2	2 x 24w T5 Indirect/Direct Module c/w Cat 2 Louvre
FLRA664x14T5-CW3	4x14w Indirect/Direct Module c/w White Broadspread Louvre

Single lamp version also available. Please state whether perforated or solid lampcover is required

FLRC662x40PLL	2 x 40 w PLL Indirect Module
FLRC662x55PLL	2 x 55 w PLL Indirect Module



Construction

Fabricated zinc plated sheet steel body with perforated or solid fronts. The category two unit also incorporates a slim category two louvre in the centre for the additional light and effect. Utilising two 40 or 55 watt PLL lamps, or T5 14 or 24 watt lamps to give high light output and high efficiency (a 4 x 14 version is also available). All gear is mounted on a removable gear tray and each unit is available with dimming control gear and integral emergency pack.

Options

Part Number	Description
HF	All fittings are high frequency
HFD	High frequency Dimmable Gear – available for all models
EM3	Emergency Pack to run 1 lamp for 3 hours

Dimensions (mm)

	A	B	Depth
FLRA	595	595	140
FLRC	595	595	140

