



Description

Our fully boxed powder coated recessed modules, suitable for 25 & 15mm Tee ceiling systems. Our products sit on the back of the (38 or 30mm) Tee for speed of installation. All attachments are lift and tilt and sit on the bottom of the Tee section.

Features


- Fully boxed & powder coated
- Fused terminal block
- Slim design

Applications

- Offices
- Factories
- Corridors
- Shopping Malls

Product Range and Ordering Details

Part Number	Nominal Dimensions	No & Wattage of Tubes	Weight Kg
FLRB632	600 x 300	2 x 18 w	2.50
FLRB662	600 X 600	2 x 18 w	3.60
FLRB663	600 x 600	3 x 18 w	4.00
FLRB664	600 x 600	4 x 18 w	4.00
FLRB1232	1200 x 300	2 x 36 w	4.00
FLRB1262	1200 x 600	2 x 36 w	6.00
FLRB1263	1200 x 600	3 x 36 w	6.50
FLRB1264	1200 x 600	4 x 36 w	7.50
FLRB1863	1800 x 600	3 x 70 w	14.00
FLRB1864	1800 x 600	4 x 70 w	14.00
FLRE664	600 x 600	4 x 18 w	4.10



Construction

Manufactured from sheet steel which is punched, folded and welded to give a fully boxed construction, then polyester powder coated white. Component specification is high and includes quality control gear, power factor correction, fused terminal block and Phillips starter switches. All components are BS approved.

Euro Module

The Euro module is similar in construction to the standard recessed modules, its difference is it incorporates deeper side flanges so the louvre and body are packed together. These also incorporate the receptacles for the wishbones springs of the louvre. The louvre is a fully trimmed unit which has full end caps to give that extra quality appearance at a competitive cost. The louvre is fixed via 4 wishbone springs and has the added advantage of suiting 15 or 25mm T bar systems.

Options

Description	Suffix
Integral Three Hour Maintained Emergency Pack	EM3
High Frequency Control Gear	HF
High Frequency Dimmable Control Gear	HFD*
Air Handling (40 litres per second)	AH

Attachments

Description	Suffix
Category One Louvre	CT1
Category Two Louvre	CT2
Category Three Louvre	CT3
Low Brightness Louvre	LBX
TPB Prismatic	PR
TPA Fire Rated Prismatic	PRF

Please specify T size required at time of ordering

Dimensions

Fitting	A	B	C
600x300	610	590	290
600x600	610	590	590
1200x300	1220	1190	290
1200x600	1220	1190	590
1800x600	1786	1810	590