


# Classic LedLite CC

IP65 DECORATIVE CIRCULAR LUMINAIRE FOR INTERNAL AND EXTERNAL APPLICATIONS



## APPLICATIONS

- > External Walkway and Patio Light
- > External under soffit and access corridor lighting
- > Corridor and Stairwell Lighting
- > Entrance Lobbies
- > Bathrooms and Toilets
- > Store Rooms

## FEATURES

- > IP65 Polycarbonate Decorative Circular Luminaire suitable for internal & external use
- > Energy efficient with high output LED light source
- > Dual circuit PCB to enable background comfort light
- > Variable output options
- > Plug-in connector for mains supply
- > Easy fit snap-on diffuser
- > Quick release gear tray
- > Finished with white trim
- > Compatible with occupancy and daylight control systems, either integrally mounted or remote
- > Available with integral LiFePO4 Lithium Battery Emergency Back-up system



## DESCRIPTION

The Classic is an IP65 Circular Decorative Luminaire that has been designed for use in residential and commercial applications, providing energy efficient LED lighting with high output illumination. The luminaire is constructed with a polycarbonate body, hinged gear tray - finished with white trim and semi-transparent or opal polycarbonate diffuser.

The Classic incorporates the LedLite CC LED PCB, providing a lifespan in the region of 100,000 hours.

**Classic LedLite CC-3/1-MicroMac** - twin Circuit LedLite LED PCB and Drivers to enable switching

by the MicroMac Microwave Detector at full output only during occupancy, with low wattage secondary circuit providing permanent comfort light when unoccupied. Supplied with Semi-transparent Diffuser.

**Classic LedLite CC-Dali Dim** - Linked Single Circuit LedLite LED PCB for dimming operation from the dimmable driver to be operated by integral detector or remote dimmer switch and supplied. Supplied with Semi-transparent Diffuser.

**Classic LedLite CC-MicroMac** - Linked Single Circuit LedLite LED PCB and Driver to enable complete "On/Off" switching by the MicroMac

Microwave Occupancy Detector of the linked circuits. Supplied with Semi-transparent Diffuser.

**Classic LedLite CC** - Linked Single Circuit LedLite LED PCB and Driver to enable complete "On/Off" switching by remote switch of the linked circuits. Supplied with Semi-transparent Diffuser.

Also available is the **Classic LedLite CC-Triac Dim** to enable dimming from a recommended remote dimmer switch - Classic LedLite Eco for areas where high performance is not essential.

## TECHNICAL + OPTIONS

MODEL CODE	WATTAGE	LAMP LUMEN OUTPUT	TRIM COLOURS	COLOUR TEMPERATURE	OVERALL SIZE	OPTION CODE SUFFIX
Classic LedLite CC 20W	20W	1770 lm	White	3000k 4000k*	ø 325 mm x 130 mm H	OP - Opal Diffuser EM3/LP4 - Integral Emergency Pack
Classic LedLite CC 23W	23W*	2035 lm				
Classic LedLite CC 25W	25W	2260 lm				

\*Default specification.