

Impala LedLite CC


A LOW PROFILE, ROBUST VANDAL RESISTANT IP65 CIRCULAR LUMINAIRE FOR INTERNAL AND EXTERNAL APPLICATIONS



Skirt also available in black



Eyelid also available in white



APPLICATIONS

- > External Walkway, Under Soffit and Patio Lighting
- > Access Corridor and Stairwell Lighting
- > Entrance Lobbies and Store Rooms
- > Bathrooms and Toilets

FEATURES

- > Low Profile IP65 Polycarbonate Decorative Circular Luminaire for internal & external use
- > 4 side entry conduit points
- > Clip-on rings for Eyelid feature, Skirt trim and all available in black or white
- > Energy efficient high output LED light source
- > Dual circuit PCB to enable background comfort light
- > Variable output options
- > Plug-in connector for mains supply
- > Diffuser fixed with security screws
- > Easy to remove gear tray
- > Finished with white trim and opal diffuser
- > Compatible with occupancy and daylight control systems, either integrally mounted or remote
- > Available with integral emergency battery back-up



DESCRIPTION

A Low Profile IP65 Circular Decorative Luminaire designed for applications requiring robust vandal resistant fittings for both internal and external use, providing energy efficient LED lighting with high output illumination. The luminaire is constructed with a polycarbonate body, integral gear tray - finished with white trim and Opal polycarbonate diffuser fixed in place with security screws. To facilitate conduit entry there are 4 x side access points positioned evenly around the base of the luminaire.

An important aspect of the Impala is the incorporation in the design of the clip-on ring providing flexibility of appearance with options of Eyelid or Skirt feature in Black or White.

The Impala incorporates the LedLite CC LED PCB, providing a lifespan in the region of 100,000 hours.

Impala LedLite CC-3/1-MicroMac - twin Circuit LedLite LED PCB and Drivers to enable switching by the MicroMac Microwave Detector at full output only during occupancy, with low wattage secondary circuit providing permanent comfort light when unoccupied. Supplied with Opal Diffuser.

Impala LedLite CC-Dali Dim - Linked Single Circuit LedLite LED PCB for dimming operation from the dimmable driver to be operated by integral detector or remote dimmer switch. Supplied with Opal Diffuser.

Impala LedLite CC-MicroMac - Linked Single Circuit LedLite LED PCB and Driver to enable complete "On/Off" switching by the MicroMac Microwave Occupancy Detector of the linked circuits. Supplied with Opal Diffuser.

Impala LedLite CC - Linked Single Circuit LedLite LED PCB and Driver to enable complete "On/Off" switching by remote switch of the linked circuits. Supplied with Opal Diffuser.

Also available is the **Impala LedLite-CC Triac Dim** to enable dimming from a recommended remote dimmer switch - **Impala LedLite Eco** for areas where high performance is not essential.

TECHNICAL + OPTIONS

MODEL CODE	WATTAGE	LAMP LUMEN OUTPUT	TRIM COLOURS	COLOUR TEMPERATURE	OVERALL SIZE	OPTION CODE SUFFIX
Impala LedLite CC 16W	16W	1600 lm	White* Black with clip-on ring	3000k 4000k*	ø 310 mm x 87 mm H	SKBLK - Skirt Trim Black SKWH - Skirt Trim White ELIDBLK - Eyelid Black ELIDWH - Eyelid White EM3 - Integral Emergency Pack PC - Photocell
Impala LedLite CC 18W	18W*	1800 lm				
Impala LedLite CC 20W	20W	2020 lm				

*Default specification.