



Pyramid LedLite CC

DECORATIVE SQUARE LUMINAIRE WITH CIRCULAR DIFFUSER
FEATURE FOR BOTH RECESSED AND SURFACE MOUNT APPLICATIONS



DESCRIPTION

The Pyramid is a Square Decorative Luminaire that has been designed for use in residential and commercial applications providing energy efficient lighting with high output illumination. The luminaire is constructed from steel with a square either recessing into a 600mm x 600mm ceiling grid with tegular edge drop front or for surface mounting. It is supplied with a quick release gear tray and finished in satin white powder coat. The Pyramid features perforations in each corner, which can be covered integrally with coloured gel film, allowing for colour light wash through the perforations. The surface mount model has chamfered edging and both designs are fitted with a circular 415mm prismatic diffuser.

The Pyramid incorporates the LedLite CC LED PCB, providing a lifespan in the region of 100,000 hours.

Pyramid LedLite CC-3/1-MicroMac - twin Circuit LedLite LED PCB and Drivers to enable switching by the MicroMac Microwave Detector at full output only during occupancy, with low wattage secondary circuit providing permanent comfort light when unoccupied. Supplied with Clear Prismatic Diffuser.

Pyramid LedLite CC-Dali Dim - Linked Single Circuit LedLite LED PCB for dimming operation from the dimmable driver to be operated by integral detector or remote dimmer switch and supplied with Clear Prismatic Diffuser.

APPLICATIONS

- > Corridor Lighting
- > Stairwells
- > Reception and Entrance Lobbies
- > Lounges

FEATURES

- > Energy efficient with high output LED light source
- > Dual circuit PCB to enable background comfort light
- > Variable output options
- > Plug-in connector for mains supply
- > 600mm x 600mm square decorative luminaire with a vented body to disperse heat and quick release gear tray
- > 4 cornered perforation design feature that can be covered integrally with gel film for colour wash
- > Available in white satin trim
- > Compatible with occupancy and daylight control systems, either integrally mounted or remote
- > Available with integral LiFePO4 Lithium Battery Back-up system



Pyramid LedLite CC-MicroMac - Linked Single Circuit LedLite LED PCB and Driver to enable complete "On/Off" switching by the MicroMac Microwave Occupancy Detector of the linked circuits. Supplied with Clear Prismatic Diffuser.

Pyramid LedLite CC - Linked Single Circuit LedLite LED PCB and Driver to enable complete "On/Off" switching by remote switch of the linked circuits. Supplied with Clear Prismatic Diffuser.

Also available is the **Pyramid LedLite CC-Triac Dim** to enable dimming from a recommended remote dimming switch.

TECHNICAL + OPTIONS

MODEL CODE	WATTAGE RECESSED / SURFACE	LAMP LUMEN OUTPUT	TRIM COLOURS	COLOUR TEMPERATURE	OVERALL SIZE	OPTION CODE SUFFIX
Pyramid LedLite CC 22W	22W	2000 lm	White	3000k 4000k*	Recessed version: 595 mm ø x 110 mm (of which 60mm is recessed)	SM - Recessed Fitting OPR - Opal Diffuser 15mm - 15mm Grid EM3/LP4 - Integral Emergency Pack
Pyramid LedLite CC 26W	26W*	2200 lm				
Pyramid LedLite CC 28W	28W	2460 lm			Surface version: 600 mm ø x 110 mm	

*Default specification.