

# Liteflow Flexistrip

FLEXIBLE COB LED STRIP FOR CONTINUOUS LIGHT OUTPUT



## APPLICATIONS

- > Edge Lighting
- > Cabinets
- > Under work tops
- > Retail
- > Plinth Lighting
- > Staircases
- > Building Feature Lighting



## DESCRIPTION

With the LiteFlow Flexistrip up to 10-metre runs are achievable using a 200W LED driver. With cut points every 60mm

It can be made to suit many applications.

The LiteFlow Flexistrip gives a continuous light emission with no 'spotting' that is experienced with other forms of LED strip.

Direct mount or a wide range of mounting profiles are available depending on the application.

## DRIVERS

DRIVER	WATTAGE	OUTPUT	IP RATING
ELG-200-24V-(D)	200 Watts	24VDC	IP65
LPV-150-24V-(D)	150 Watts	24VDC	IP65
LPV-150-24V-(D)	100 Watts	24VDC	IP65
DR-CV-60-24V-(D)	60 Watts	24VDC	IP20 / IP65
DR-CV-40-24V-(D)	40 Watts	24VDC	IP20 / IP65

## TECHNICAL + OPTIONS

MODEL CODE	WATTAGE	VOLTAGE	LAMP LUMEN OUTPUT	COLOUR TEMPERATURE	CRI	OVERALL SIZE	OPTION CODE SUFFIX
LITEFLOW FLEXISTRIP	15 Watts/MTR	24VDC	90 lm/w	3000K 4000K 6000K	CRI80	5000mm (W) x 10mm (D)	D - Dimmable

\*Default specification.