
Viscount LTM-EM3

LED EMERGENCY BULKHEAD - IP65 ROBUST FITTING







DESCRIPTION

High performance emergency bulkhead constructed with a white polycarbonate back body and semi transparent diffuser.

It is designed for either surface or semi-recessed mounting.

The versatility of design offers a fitting that is universal for maintained and non-maintained, suitable for escape route lighting and escape route signage with configurable legends included as standard and is rated to IP65 for both internal and external applications.

APPLICATIONS

- > Schools, hospitals, commercial buildings, industrial buildings, residential
- > External walkways
- > Emergency exit routes
- > Emergency exit doors

FEATURES

- > BS 60598-2-22 and ISO 7010 compliant
- > LIA certified
- > IP65
- > IK10 impact rating
- > Low stand-by power consumption < 0.5W (NM)
- > Self-test version available
- > Lithium battery
- > Maintained or non-maintained configurations
- > Suitable for indoor or outdoor applications
- > Surface or recessed mount
- > Hinged internal back plate for ease of wiring
- > 5-year warranty

SPECIFICATION

- > Input voltage / frequency 220-240V AC 50Hz
- > Discharge duration 3-hours
- > Charge duration <24-hours
- > Battery type Li-Ion 3.6V 2.5Ah
- > Housing Polycarbonate
- > Diffuser Polycarbonate



TECHNICAL + OPTIONS

MODEL CODE	WATTAGE	LAMP LUMEN OUTPUT	OPERATING TEMPERATURE	TRIM COLOUR	OVERALL SIZE	OPTION CODE SUFFIX
VISCOUNT LTM-EM3	0.5W NM 3W M	170 lm	0-40°C	Matt White	109 mm (H) x 355 mm (W) x 60.8 mm (D)	ST - Self Test

^{*}Default specification.